

MINI-CLIK®

Sensor: **Rain**

FEATURES

- Easily installs on any automatic irrigation system
- Debris tolerant for reliable operation without unnecessary shutdowns
- Can be set to shut system off from 3 mm to 19 mm of rainfall
- Includes 7.6 m of 0.5 mm² sheathed, two-conductor, UL-approved wire
- Optional user-installed metal gutter mount for Mini-Clik (order SGM, Includes Mini-Clik)
- Warranty period: 5 years

SPECIFICATIONS

- Switch rating: 24 VAC, 5 A
- Wiring: 0.5 mm², typically interrupts the common ground wire between the solenoid valves and controller

MINI-CLIK®	
Model	Description
MINI-CLIK	Rain Sensor
MINI-CLIK-NO	Rain Sensor with “normally-open” switch
MINI-CLIK-C	Rain Sensor with conduit mount
MINI-CLIK-HV	Rain Sensor for high voltage application (120/230 VAC)



MINI-CLIK
Height: 5 cm
Length: 15 cm



SG-MC
Stainless steel sensor guard enclosure for Mini-Clik. Includes Mini-Clik.



SGM
Optional gutter mount

FREEZE-CLIK®

Sensor: **Freeze**

FEATURES

- Installs easily with no adjustment needed
- Accurate temperature sensing shuts system off when air temperature reaches 3° C
- Used with other sensors to enhance overall efficiency of irrigation systems
- Warranty period: 5 years

SPECIFICATIONS

- Switch rating: 24 VAC, 5 A
- Wiring: Typically interrupts the common ground wire between the solenoid valves and the controller
- UL listed

* Not intended for agricultural applications

FREEZE-CLIK®	
Model	Description
FREEZE-CLIK	Freeze sensor interrupts irrigation when temperatures drop below 3° C
FREEZE-CLIK REV	Freeze sensor allows irrigation when temperatures drop below 3° C



FREEZE-CLIK
Height: 5 cm
Length: 11 cm