

# E65 / E75 / E83 TRAC M



If any of these parts are worn or damaged, replace them or contact technical assistance.

## DAILY CHECKLIST



1. Take the machine to a suitable area for the disposal of waste water and turn it off. The brake will activate automatically.

2. Unclip the drain hose.

3. Remove the hose cap and empty the recovery tank.

4. Empty and clean the debris collection basket.

5. Rinse out the recovery tank and clean the tank overflow prevention float.



6. Rinse out the vacuum hose.

7. Check that the vacuum motor filter is clean.

8. Clean the squeegee and squeegee blades.

9. Clean the splash guard skirts.

10. Check the battery charge level and put the machine on charge if necessary.

## WEEKLY CHECKLIST



11. Once charging is complete, check the level of electrolytes in the battery and if necessary, add distilled water (only for lead acid batteries).

1. Clean the solution filter.

2. Clean the vacuum motor filter.

3. Check for wear on the squeegee blades, rotate or replace them if necessary.



4. Inspect the brushes to make sure they are clean and in good condition. If the bristle length is close to the wear indicator (red color), replace the brush.

5. Check that the gasket in the tank lid is in good condition.

6. Verify that the self-levelling splash guard is free to move, and that the skirts are in good condition.

7. Inspect the drain hose and vacuum hose for damage, which can result in leaks.