

PRO-SPRAY®

Models: **Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm**
 Inlet: 1/2"

FEATURES

- Models: Shrub, 5 cm, 7.5 cm, 10 cm, 15 cm, 30 cm
- Compatible with all female threaded nozzles
- Side inlet (SI) version available in 15 cm and 30 cm
- Innovative directional flush plug design
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve

OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa

FACTORY INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation)
- Check valve available on 10 cm, 15 cm, 30 cm
- Reclaimed water ID cap

USER INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation; P/N 437400)
- Reclaimed water ID cap (P/N 458520)
- Snap-on reclaimed cover (P/N PROSRCCAP)
- ▶ = *Advanced Feature descriptions on page 60*



Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps.

PRO-SPRAY - SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
PROS-00 = Shrub Adapter	(blank) = No option
PROS-02 = 5 cm Pop-up	CV = Factory-installed drain check valve (Pop-up models only, 15 cm and 30 cm models ordered as CV will come as no side inlet)
PROS-03 = 7.5 cm Pop-up	R = Factory-installed reclaimed body cap (shrub molded in purple)
PROS-04 = 10 cm Pop-up	
PROS-06-SI = 15 cm Pop-up with side inlet	
PROS-06 = 15 cm Pop-up (no side inlet)	
PROS-12-SI = 30 cm Pop-up with side inlet	
PROS-12 = 30 cm Pop-up (no side inlet)	

Examples:

- PROS-04** = 10 cm Pop-up
- PROS-06 - CV** = 15 cm Pop-up, drain check valve
- PROS-12 - CV - R** = 30 cm Pop-up, drain check valve, reclaimed body cap



PROS-00
 Retracted height: 4 cm
 Inlet size: 1/2"



PROS-02
 Retracted height: 10 cm
 Pop-up height: 5 cm
 Exposed diameter: 5.7 cm
 Inlet size: 1/2"



PROS-03
 Retracted height: 12.5 cm
 Pop-up height: 7.5 cm
 Exposed diameter: 5.7 cm
 Inlet size: 1/2"



PROS-04
 Retracted height: 15.5 cm
 Pop-up height: 10 cm
 Exposed diameter: 5.7 cm
 Inlet size: 1/2"



[A] PROS-06-SI
[B] PROS-06
 Retracted height: 22.5 cm
 Pop-up height: 15 cm
 Exposed diameter: 5.7 cm
 Inlet size: 1/2"



[A] PROS-12-SI
[B] PROS-12
 Retracted height: 41 cm
 Pop-up height: 30 cm
 Exposed diameter: 5.7 cm
 Inlet size: 1/2"



SPRAYS